

WHAT IS CLAIMED IS:

1. A system for mixing water with CO₂ to produce carbonated water at a targeted carbonation level, the system comprising:
 - a tank containing water and a headspace, the tank having a first end and a second end;
 - a source of CO₂ in fluid communication with the headspace;
 - a baffle in the tank between the first end and the second end;
 - an orifice in the first end of the tank; and
 - a supply of water coupled to the orifice, the orifice being structured and arranged to direct a stream of water into the tank,
 - wherein the baffle is positioned in the tank so as to target a desired carbonation level of the water in the tank.
2. The system of claim 1, further comprising an outlet at the first end of the tank.
3. The system of claim 2, wherein an outlet tube extends from the first end past the baffle, and wherein the baffle includes a cutout region structured and arranged to accommodate the outlet tube.
4. The system of claim 1, further comprising a CO₂ inlet member and a pressure relief member each extending from the second end through the baffle.
5. The system of claim 4, wherein the baffle includes at least one opening configured to receive at least one of the CO₂ inlet member and the pressure relief member.
6. The system of claim 1, further comprising:

a probe housing extending from the second end of the tank toward the baffle;
a liquid level probe in the probe housing, the liquid level probe extending
through the baffle and toward the first end.

7. The system of claim 6, wherein the baffle is coupled to the probe
housing.

8. The system of claim 6, wherein the baffle includes an opening
structured and arranged to accommodate the liquid level probe.

9. The system of claim 8, wherein the probe housing extends through the
opening in the baffle and toward the first end of the tank.

10. The system of claim 1, wherein the baffle is structured and arranged so
as to atomize the stream of water when the level of the carbonated water reaches a
predetermined low level.

11. The system of claim 1, wherein the baffle is structured and arranged so
as to agitate carbonated water flowing by the baffle when the level of the carbonated
water reaches a predetermined low level.

12. The system of claim 1, wherein the orifice is configured to direct the
stream of water such that CO₂ bubbles are entrained to produce the targeted
carbonation level of the water.

13. A carbonator for use in a beverage dispenser, comprising:
a tank having a first end and a second end, the tank being configured
to contain water;

an inlet in the second end of the tank configured to receive a supply of
CO₂;

LAW OFFICES

INNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

a baffle in the tank between the first end and the second end; and
an orifice in the first end of the tank, the orifice being structured and
arranged to direct a stream of water into the tank,

wherein the baffle is positioned in the tank so as to target a desired
carbonation level of the water in the tank.

14. The carbonator of claim 13, further comprising an outlet at the first end
of the tank.

15. The carbonator of claim 14, wherein an outlet tube extends from the
first end past the baffle, and wherein the baffle includes a cutout region structured
and arranged to accommodate the outlet tube.

16. The carbonator of claim 13, further comprising a CO₂ inlet member and
a pressure relief member each extending from the second end through the baffle.

17. The carbonator of claim 16, wherein the baffle includes at least one
opening configured to receive at least one of the CO₂ inlet member and the pressure
relief member.

18. The carbonator of claim 13, further comprising:
a probe housing extending from the second end of the tank toward the baffle;
a liquid level probe in the probe housing, the liquid level probe extending
through the baffle and toward the first end.

19. The carbonator of claim 18, wherein the baffle is coupled to the probe
housing.

20. The carbonator of claim 18, wherein the baffle includes an opening
structured and arranged to accommodate the liquid level probe.

21. The carbonator of claim 20, wherein the probe housing extends through the opening in the baffle and toward the first end of the tank.

22. The carbonator of claim 13, wherein the baffle is structured and arranged so as to atomize the stream of water when the level of the carbonated water reaches a predetermined low level.

23. The carbonator of claim 13, wherein the baffle is structured and arranged so as to agitate carbonated water flowing by the baffle when the level of the carbonated water reaches a predetermined low level.

24. The carbonator of claim 13, wherein the orifice is configured to direct the stream of water such that CO₂ bubbles are entrained to produce a desired carbonation of the water.

25. A method of mixing water with CO₂ to produce carbonated water at a targeting carbonation level, the method comprising:

supplying gaseous CO₂ to a headspace in a tank containing a volume of water to be carbonated, said headspace being disposed above a liquid-gas interface between the water and the gaseous CO₂;

directing a stream of water first through the headspace to entrain CO₂ gas therein and then into the volume of water to carbonate the same to a desired carbonation level; and

separating CO₂ bubbles formed in the quantity of water according to relatively large and small sizes.

26. The method of claim 25, wherein said separating is performed by a baffle disposed in the quantity of water in the tank in a path of the stream of water,

LAW OFFICES

INNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

and between the stream and a carbonated water outlet from the tank, whereby most large size bubbles become trapped on the stream side of the baffle and never reach the carbonated water outlet.

27. The method of claim 26, wherein the baffle is structured and arranged to atomize the stream of water when the quantity of water in the tank reaches a predetermined level.

28. The method of claim 26, wherein the baffle is structured and arranged to agitate water as it flows from the stream side of the baffle to the carbonated water side of the baffle when the quantity of water in the tank reaches a predetermined level.

29. The method of claim 26, further comprising adjusting a position of the baffle to target a desired carbonation level of the water in the tank.

30. A method of dispensing a beverage, comprising:
producing carbonated water according to the method of claim 25; and
mixing an amount of concentrate with an amount of the carbonated water to produce a beverage; and
dispensing the beverage.

31. A carbonator for use in a beverage dispenser, comprising:
a tank having at least one wall, the tank being configured to contain water;
an inlet in the at least one wall of the tank configured to receive a supply of CO₂;
a baffle in the tank spaced from the inlet;

LAW OFFICES

INNEGAN, HENDERSON,
FARABOW, GARRETT,
& DUNNER, L.L.P.
1300 I STREET, N. W.
WASHINGTON, DC 20005
202-408-4000

an orifice in the at least one wall of the tank, the orifice being structured and arranged to direct a stream of water into the tank, wherein the baffle is positioned in the tank so as to target a desired carbonation level of the water in the tank.

the tank wall with the orifice being positioned in the tank so as to target a desired carbonation level of the water in the tank.